



CONIX®MONO










CONIX®MONO

The single wall CONIX®MONO chimney system safely resolves any smoke exhaust problem for civil and industrial systems, from the smallest home boiler to cogenerators for heating plants with any type of fuel.



CONIX®MONO chimney system is made up of AISI 316L









The 5 benefits of Conix®



Seal against fumes and condensation



No silicone gaskets and no risks associated with deterioration of the same



Better flue draught pressure



Quick and easy installation



Universal use

Conix®, safety at all times

CONIX® is the revolutionary flue system made of stainless steel with conical coupling patented in Europe. It can work in a safe and efficient manner in all conditions, without need for gaskets or clamps on its components, and is quick and easy to install.

The various parts of the CONIX® System are joined using a simple welding procedure. As no gaskets or clamps are needed, the system can be installed in half the time and with great ease, the pipes in particular.

Innovation by vocation

The sturdiness, benefits and guaranteed qualities of the new CONIX® system have motivated Camini Wierer to take a bold step: to discard the old system with couplings once and for all. This is a radical decision based on the

total safety and trustworthiness of the product, a strategic aim so important as to now feature on the product logo; and a commercial venture that will see Camini Wierer phasing out silicone gaskets completely by 10.10.2010.





•

INSTALLATION OVERVIEW

KI060 KI062 Anti-backflow termina with locking band AI040 Tapered terminal Protection sleeve AI052 Guy wire clamp AI046 Flashing AIL41: 0 - 25° AIL43: 25 - 45° AIL45: 0° MULTI INLET CHIMNEYS FOR TYPE C APPLIANCES Extetions for code Al055 Al021: 110 - 230mm Al022: 230 - 350mm Al023: 055 - 100mm KI082 AI055 KI066 Tee reduced to 80mm (WNI female adapter) AI056 Reinforces for code Al055 KI095 KI067 Tee reduced to 80mm with hole for measurament devices Extentions for code Al051 Al015: 110 - 230mm Al016: 230 - 350mm AI051 Straight chimney sections KI091: H = 944 mm KI093: H = 444 mm KI194: H = 194 mm KI019 Al258: 25mm, 110kg/mc Pressure equalising opening AIP51: 50-100mm Extensions for code Al051 KI007 Element for cut pipe KI097 AI012 Adjustable elbow 0-90° KI050 Locking band KI017: without seal KIG17: with seal KI090 KI190 (sp.10/10) chimney section for relining KI071 KI170 KI179: 3° KI073: 15° KI074: 30°

Available diameters - internal measurements (mm):

0

Joint elements KI025: 80 mm (sleeve) KI026: 100 mm (sleeve) KI027: 120 mm (sleeve) KI030: Ø-4mm (sleeve)

Inspection with plug "T600-H1-W

Condensate drain support

KI072

KI077 Condensate drain


AI018

KI075: 45° KI076: 87°

KIN98: T450-N1-D KIP98: T160-P1-W KI013

KI096

KI033 Plug for cascade



Product ID

Description of product T600-H1-W-V2-L50040-G



AI054 Pulling band

AI004 Beating plate







(



(